

MultiRAE

Wireless portable six-gas monitor with advanced VOC detection capability

The MultiRAE is the most advanced portable chemical detector on the market. The MultiRAE delivers the broadest PID sensor range in its class and the versatility to support 25 intelligent interchangeable sensor options (such as PID, NDIR for combustibles and CO₂, ammonia, chlorine, formaldehyde, and phosphine) to fully meet the monitoring needs in a variety of applications, including industrial hygiene, personal protection, leak detection, and HazMat response.

The MultiRAE's optional wireless capability improves safety by providing commanders and safety of cers real-time access to instrument readings and alarm status from any location¹ for better situational awareness and faster incident response.



MultiRAE used for worker exposure monitoring at an oil refinery

APPLICATIONS

- Industrial hygiene, personal protection, and leak detection in industries such as:
 - Aviation (wingtankentry)
 - Chemical
 - Environmental
 - Oil and gas
 - Pharmaceutical
 - Shipping/marine
- HazMat response
- Clandestine drug labs

- *Highly versatile and customizable*
- *Best PID in its class (0 to 5,000 ppm range, 0.1 ppm resolution)*
- *Man Down Alarm with real-time remote wireless notification*
- *Compliant with MIL-SPEC-810G performance standard*
- *Fully automatic bump testing and calibration with AutoRAE 2*

FEATURES & BENEFITS

- Wireless access to real-time instrument readings and alarm status from any location¹
- Unmistakable five-way local and remote wireless notification of alarm conditions, including Man Down Alarm¹
- Intelligent sensors store calibration data, so they can be swapped in the field²
- Extensive on-board gas libraries (190 VOCs and 55 combustible gases)
- Largest display in its class
- Continuous datalogging (6 months for 5 sensors, 24x7)
- Device Management with Honeywell SafetySuite

MultiRAE Specifications

INSTRUMENT SPECIFICATIONS ⁴	
SIZE	7.6" H x 3.8" W x 2.6" D (193 x 96.5 x 66 mm)
WEIGHT	31 oz (880 g)
SENSORS	25 intelligent interchangeable field-replaceable sensors including PID for VOCs, electrochemical sensors for toxic gases and oxygen, combustible LEL and NDIR sensors, and CO ₂ NDIR sensor
BATTERY OPTIONS, RUNTIME ⁵ AND RECHARGE TIME	- Rechargeable Li-ion (~12-hr. runtime, < 6-hr. recharge time) - Extended duration Li-ion (~18-hr. runtime, < 9-hr. recharge time) - Alkaline adapter with 4 x AA batteries (~6-hr. runtime)
DISPLAY	Monochrome graphical LCD display (128 x 160) with backlighting. Automatic screen "flip" feature.
DISPLAY READOUT	- Real-time reading of gas concentrations; PID measurement gas and correction factor; Man Down Alarm on/off; visual compliance indicator; battery status; datalogging on/off; wireless on/off and reception quality. - STEL, TWA, peak, and minimum values
KEYPAD BUTTONS	3 operation and programming keys (Mode, Y/+, and N/-)
SAMPLING	Built-in pump. Average flow rate: 250 cc/min. Auto shutdown in low-flow conditions
CALIBRATION	Automatic with AutoRAE 2 Test and Calibration System or manual
ALARMS	Wireless remote alarm notification; audible (95 dB @ 30 cm), vibration, visible (flashing bright red LEDs), and on-screen indication of alarm conditions - Man Down Alarm with pre-alarm and real-time remote wireless notification ¹
DATALOGGING	Continuous datalogging (6 months for 5 sensors at 1-minute intervals, 24/7) - User-configurable datalogging intervals (from 1 to 3,600 seconds)
COMMUNICATION AND DATA DOWNLOAD	- Data download and instrument set-up and upgrades on PC via desktop charging and PC comm. cradle, travel charger, or AutoRAE 2 Automatic Test and Calibration System - Wireless data and alarm status transmission via built-in RF modem (optional)
WIRELESS NETWORK	ProRAE Guardian Real-Time Wireless Safety System or EchoView Host-based Closed-Loop System
WIRELESS RANGE (TYPICAL)	MultiRAE to RAElink3 (Z1) Mesh modem ~330 feet (100 meters) MultiRAE to EchoView Host, RAEMesh Reader or RAEPoint ~660 feet (200 meters) MultiRAE to Wi-Fi Access Point ~330 feet (100 meters)
OPERATING TEMPERATURE	-4° to 122°F (-20° to 50°C)
HUMIDITY	0% to 95% relative humidity (non-condensing)
DUST AND WATER RESISTANCE	IP-65 ingress protection rating (dust-tight and waterproof against hosing jets coming from all directions)
SAFETY CERTIFICATIONS	CSA: Class I, Division 1, Groups A, B, C and D, T4 Class II, Division 1; Groups E, F, G; T85°C ATEX: 0575 II 1G Ex ia IIC T4 Ga 2G Ex ia d IIC T4 Gb with IR Sensor installed I M1 Ex ia I Ma IECEX: Ex ia IIC T4 Ga Ex ia d IIC T4 Gb with IR Sensor installed I M1 Ex ia I Ma IECEX/ANZEX: Ex ia IIC T4 Ga Ex ia d IIC T4 Gb with IR Sensor installed Ex ia I Ma
EMC/RFI	EMC directive: 2004/108/EC
PERFORMANCE TESTS	MIL-STD-810G and 461F compliant. LEL CSA C22.2 No. 152; ISA-12.13.01
LANGUAGES	Arabic, Chinese, Czech, Danish, Dutch, English, French, German, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, and Turkish
WARRANTY	- Four years on Liq O ₂ sensors - Three years on CO and H ₂ S sensors - Two years on non-consumable components and catalytic LEL sensors - One year on all other sensors, pump, battery, and other consumable parts
WIRELESS FREQUENCY	ISM license free band. IEEE 802.15.4 Sub 1GHz, Wi-Fi 802.11 b/g
WIRELESS APPROVALS	FCC Part 15, CE R&TTE, Others ⁶
RADIO MODULE	Supports RM900A

SENSOR SPECIFICATIONS ⁴	RANGE	RESOLUTION
PID SENSORS		
VOC 10.6 EV (EXT. RANGE)	0 to 5,000 ppm	0.1 ppm
COMBUSTIBLE SENSORS		
CATALYTIC LEL	0 to 100% LEL	1% LEL
NDIR (0-100% LEL METHANE)	0 to 100% LEL	1% LEL
NDIR (0-100% VOL. METHANE)	0 to 100% Vol.	0.1% Vol.
CARBON DIOXIDE SENSOR		
CARBON DIOXIDE (CO ₂) NDIR	0 to 50,000 ppm	100 ppm
ELECTROCHEMICAL SENSORS		
AMMONIA (NH ₃)	0 to 100 ppm	1 ppm
CARBON MONOXIDE (CO)	0 to 500 ppm	1 ppm
CARBON MONOXIDE (CO), EXT. RANGE	0 to 2,000 ppm	10 ppm
CARBON MONOXIDE (CO), H ₂ -COMP.	0 to 2,000 ppm	10 ppm
CARBON MONOXIDE (CO) +	0 to 500 ppm	1 ppm
HYDROGEN SULFIDE (H ₂ S) COMBO	0 to 200 ppm	0.1 ppm
CHLORINE (CL ₂)	0 to 50 ppm	0.1 ppm
CHLORINE DIOXIDE (CLO ₂)	0 to 1 ppm	0.03 ppm
ETHYLENE OXIDE (ETO-A)	0 to 100 ppm	0.5 ppm
ETHYLENE OXIDE (ETO-B)	0 to 10 ppm	0.1 ppm
FORMALDEHYDE (HCHO)	0 to 10 ppm	0.05 ppm
HYDROGEN CYANIDE (HCN)	0 to 50 ppm	0.5 ppm
HYDROGEN SULFIDE (H ₂ S)	0 to 100 ppm	0.1 ppm
METHYL MERCAPTAN (CH ₃ -SH)	0 to 10 ppm	0.1 ppm
NITRIC OXIDE (NO)	0 to 250 ppm	0.5 ppm
NITROGEN DIOXIDE (NO ₂)	0 to 20 ppm	0.1 ppm
OXYGEN (O ₂)	0 to 30% Vol.	0.1% Vol.
OXYGEN (LIQ O ₂)	0 to 30% Vol.	0.1% Vol.
PHOSPHINE (PH ₃)	0 to 20 ppm	0.1 ppm
PHOSPHINE (PH ₃ H)	0 to 20 ppm	0.1 ppm
SULFUR DIOXIDE (SO ₂)	0 to 20 ppm	0.1 ppm

¹ Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.
² RAE Systems recommends calibrating sensors on installation.
³ A two-gas combination sensor is required for a 6-gas configuration.
⁴ Specifications are subject to change.
⁵ Specification for non-wireless monitors.
⁶ Contact RAE Systems for country specific wireless approvals and certificates.

ORDERING INFORMATION (MODEL: PGM-6228)

- Wireless¹ and non-wireless configurations are available
- Refer to the Portables Pricing Guide for part numbers for monitors, accessories, sampling and calibration kits, gas, sensors, and replacement parts

Device Management with
Honeywell SafetySuite



honeywellanalytics.com/SafetySuite